



DECLARATION OF PERFORMANCE No. 105/2017 ENG

According EU Construction Product Regulation No305/2011 (CPR)

PRODUCT: **SHAFT LADDERS PREFALAD**
Type PREFALAD 50x50/300 and 50x50/400

Used like:

- shaft ladders
- ladders for machinery facility

are intended for areas with higher dampness or aggressive environment. They are non liquid-absorbing, resistant against corrosion and UV radiation, light-weight, electrical non-conductive and electromagnetic transparent. It is possible to use them in direct contact with drinking water.

PRODUCER: **PREFA KOMPOZITY,a.s.**
ID: 269 49 881
Contact:
Kulkova 10, 615 00 Brno, Czech Republic, kompozity@prefa.cz, tel.:
++420 541 583 111

SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:

System 4

PRODUCT PERFORMANCE

Essential characteristics	Performance	Harmonised technical specification
Max. output height	6000 mm	EN 14396:2004
Max. distance between mounting fixings	3000 mm	EN 14396:2004
Width of rungs	300-500 mm	EN 14396:2004
Depth onset	Min. 150 mm	EN 14396:2004
Resistance against pulling	Min. 3,0 kN	EN 14396:2004
Maximum vertical load	2,6 kN	EN 14396:2004
Direct contact with drinking water	Suitable	CZ Statutory Rule 409/2005 Sb.
Electrical insulation capability	Min. 30 kV	EN 61478:2001

The performance of the product PREFALAD is in conformity with the declared performance in table above.
This declaration of performance is issued under the sole responsibility of the manufacturer.

Brno, August 10, 2017

PREFA KOMPOZITY, a.s.
Kulkova 10/4231, 615 00 Brno
IČO: 26949881, DIČ: CZ26949881


Miloš Filip
Managing Director